




ProGlide

High Performance Sliding Door

High Performance Sliding Door

The ProGlide range from Alspec has been designed with Australia's unique architecture and climate in mind. The door allows architects and designers the freedom to achieve large expansive openings without the need to compromise on performance or aesthetics.

Specifying Alspec's ProGlide range ensures the client receives a solid, durable, high performance product.



Key Features


- High water performance sill options
- Large sliding panels, ideal for housing, apartment and commercial applications
- Inside or outside sliding panels, allowing multiple panel designs
- Allows up to 4 panels stacking in each direction
- Heavy duty interlocks for high wind load requirements
- Accepts up to 13.52mm single glazed and up to 28mm double glazing units, allowing the designer to achieve the most demanding thermal and acoustic specifications
- 90 degree post free corner option
- Heavy duty rollers up to 200kg per panel
- Bevelled rail options

Technical Specifications

Frame Dimensions		Acoustic Performance		Compatible Systems	
Option 1	101 x 50mm	Glass Type	Rw (C; C _{tr})	McArthur Evo Centre Pocket Framing	
Option 2	151.5 x 50mm	6.38mm Laminate	32 (0, -2) dB	ecoFRAMEplus Centre Pocket Double Glazed Framing	
Maximum Product Performance		10.38/12/6.38 IGU	38 (-2, -4) dB	Hunter Evo Flush Glazed Framing	
SLS (Pa)	3000	Thermal Performance			
ULS (Pa)	6000	Uw range SG	4.3 - 6.1		
Water (Pa)	700	SHGC range SG	0.38 - 0.66		
Maximum Recommended Sizes		Uw range DG	3.0 - 3.9		
Height	3150mm	SHGC range DG	0.22 - 0.55		
Sash Width	2250mm	Glazing Details			
Weight	200kg per panel	Single Glazed	5 - 13.52mm		
		Double Glazed	18 - 28mm		

Typical Configurations

Double Track



Triple Track

