



# The Complete Structural System

The ecoWALL 225 Flush Glazed Framing is arguably Alspec's greatest engineering achievement.

With 225mm x 60mm profiles it is not only proportionally correct but also boasts the structural integrity of it's 250mm alternatives available in the market. Add this to the fact that with ecoWALL 225 you can single or double glaze unlike any of the competitors.

In many cases using ecoWALL 225 can eliminate the requirement of unsightly and often very expensive steel frames to support the system (this is determined subject to structural engineer's detail and project specific design criteria).

With reinforced subheads, mullion anti buckling technology, and self draining sub-sills to prevent water leakage the ecoWALL 225 is the complete structural system ideal for your next commercial foyer, auto showroom or high end residential project.

## **Typical Configurations**

F.	F.	F.	F.
F.	F.	F.	F.
F.	F.	F.	

#### **CAD Cross Sections**



#### **Key Features**

- Sharp unbroken lines
- 4 14mm single glazing and up to 28mm double glazing options
- Ideally suited for automotive showrooms, two storey foyers, atriums or similar applications
- Secure glazing using fully captive backing gaskets to outside of frame
- Superior weathering performance
- Colour coded glazing wedges for ease of identification allowing for multiple glass types

### **Technical Specifications**

#### Frame Dimensions 225 x 60mm Option 1 **Maximum Recommended Sizes** Height 6300mm Width 2700mm Maximum Product Performance SLS (Pa) 4000 ULS (Pa) 6000 Water (Pa) 1200 Acoustic Performance 6.38mm/10/ 37 (-1,-4) dB 8.38mm IGU

Thermal Performance	
Uw range SG	5.0 - 6.9
SHGC range SG	0.24 - 0.73
Uw range DG	3.5 - 4.3
SHGC range DG	0.16 - 0.63

Glazing Details	
Glass Position	Front
Single Glazed	4 - 14mm
Double Glazed	20 - 28mm

Swan Evo 45mm Commercial Shopfront Door
Torrens 45mm Commercial Shopfront Door

Compatible Systems









