




# **Awning and Casement Window**


Alspec's range of awning and casement windows are ideal for suburban housing, multi-unit residential, hotels and commercial applications. The awnings and casements can integrate with a number of Alspec Commercial Framing systems by using different awning adaptors.

The 35mm and 50mm sashes offer the benefit of overlapping internal and external seals to achieve superior weather performance. The 443 30mm sash sits inset of the framing and can offer a flush appearance.

Various glazing options for single and double glazing are available. All awnings and casements can be used with a range of available stays and operated with chainwinders or cam handles, locking or non-locking. With the use of our chainwinder adaptor, insect and security screens can easily be added from the inside of the building.

## **Typical Configurations**





#### **CAD Cross Sections**

Sill detail







#### **Key Features**

- Wide range of applications
- Integration with a number of Alspec Commercial Framing systems
- Superior weather performance
- Various glazing options including double glazing
- Electric winder option

### **Technical Specifications**

Sash width 35mm	
Sash width 50mm	
0.5	
	50mm
	1800mm
	1500mm
	40kg
1.2	1.8
35mm	50mm
1000	1000
1800	3500
300	700
35mm	50mm
35mm 5.9 - 6.9	50mm 5.8 - 7.2
5.9 - 6.9	5.8 - 7.2
5.9 - 6.9 0.26 - 0.53	5.8 - 7.2 0.29 - 0.51
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8 0.15 - 0.48	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3 0.13 - 0.45
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8 0.15 - 0.48	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3 0.13 - 0.45
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8 0.15 - 0.48 35mm 4 - 12mm	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3 0.13 - 0.45 50mm 4 - 12.38mm
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8 0.15 - 0.48 35mm 4 - 12mm 18 - 24mm	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3 0.13 - 0.45 50mm 4 - 12.38mm 24 - 30mm
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8 0.15 - 0.48 35mm 4 - 12mm 18 - 24mm	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3 0.13 - 0.45 50mm 4 - 12.38mm 24 - 30mm
5.9 - 6.9 0.26 - 0.53 4.2 - 4.8 0.15 - 0.48 35mm 4 - 12mm 18 - 24mm 35mm Rw (C; C <sub>tr</sub> )	5.8 - 7.2 0.29 - 0.51 4.3 - 5.3 0.13 - 0.45 50mm 4 - 12.38mm 24 - 30mm 50mm Rw (C; C <sub>tr</sub> )
	35mm 1500mm 1200mm 35kg 1.2 35mm 1000 1800

McArthur Evo Centre Pocket Framing

Hunter Evo Flush Glazed Framing

ecoFRAMEplus Centre Pocket Double Glazed Framing











