




# **Top Hung Awning Window**


Alspec's® range of Top Hung Awning windows are ideal for suburban housing, multi-unit residential, hotels and semi commercial applications.

The Top Hung Awnings can integrate with a number of Alspec's commercial framing systems by using different awning adaptors. The 35mm sash is available as an overlapping or inset sash. The 443 30mm sash sits inset of the framing and can offer a flush appearance. Various options for single and double glazing are available.

All Top Hung Awnings are operated with Chainwinders. With the use of our Chainwinder adaptor insect and security screens can easily be added from the inside of the building.

## **Typical Configurations**





#### **CAD Cross Sections**



## **Key Features**

- Wide range of applications
- Integration with a number of Alspec® Commercial Framing systems
- Superior weather performance
- Various glazing options

### **Technical Specifications**

Frame Dimension	ns
Option 1	Sash width 35mm
Maximum Recom	mended Sizes
Height	1500mm
Width	1200mm
Weight	40kg
Sash SQM	1.5
Maximum Produc	t Performance
SLS (Pa)	1000
ULS (Pa)	2300
Water (Pa)	300
Glazing Details	
Single Glazed	4 - 12mm
Double Glazed	18 - 24mm

Compatible Systems
McArthur
McArthur Evo
Hunter Evo







